

SINGER®

2212A



**SINGER® Two Needle Heavy Duty
Lockstitch Sewing Machine**

Highest Productivity and Superior Sewing Quality

2212A

SINGER® Two Needle Heavy Duty Lockstitch Sewing Machine



Features

- Needle feed mechanism synchronously moves with lower drop feed, ensures fine and non twisted seams from slippery or difficult to feed materials.
- By graduation dial, easy adjustment of stitch length can be obtained.
- Standard needle gauge: 1/4" (6.4 mm). Simple and quick gauge change.
- Fully rotating vertical axis hook with automatic lubricating system.
- Reverse feed by simple level operation.
- Automatic lubricating system, smooth and quiet running, easy maintenance.
- Split needle bar (some models) which allow single needle sewing at a corner with one-touch-lever operation.
- Equipped with large hook (some models), the bobbin has twice the capacity of that of a regular hook.

Specification Chart

Model	2212A141L	2212A141A	2212A541A	2212A143A	2212A543A
Fabric	Light-medium weight fabric	Medium-heavy weight fabric	Heavy weight fabric	Medium-heavy weight fabric	Heavy weight fabric
Needle Bar	Single needle	Single needle	Single needle	Two needle	Two needle
Hook	Normal hook	Normal hook	Large hook	Normal hook	Large hook
Max. Speed	4500 s.p.m.	4500 s.p.m.	4000 s.p.m.	3000 s.p.m.	3000 s.p.m.
Needle CAT.Nm			DPx5		
Max. Stitch Length	5 mm	5 mm	7 mm	5 mm	7 mm
Lift of P. Foot By Hand			7 mm		
By Knee	9 mm	9 mm	13 mm	9 mm	13 mm

SINGER®
AT HOME WORLDWIDE™